



Acrobat combines the stunning appearance of a cut pile carpet with the sheer convenience, practicality and hardwearing features of a heavy contract carpet tile.

With its cut pile tufted construction and generous pile weight of 1050gsm, Acrobat offers superior underfoot comfort and a touch of luxury, cleverly delivering the appearance of a broadloom carpet.

Available in a range of 16 modern and commercially appealing colourways, Acrobat will complement all types of commercial interiors and is particularly suitable for boardrooms, receptions and hospitality areas.

Acrobat has a 10 year guarantee which is extended to 15 years if supplied with SOFTbac® secondary backing. SOFTbac® provides additional underfoot comfort, performance longevity and improved thermal and sound insulation compared with conventional backings.

- 10 year guarantee
- Manufactured from 100% PA Anso Performa nylon 6
- Can be laid broadloom, quarter turn or tessellated
- Available in 16 colours
- Available with SOFTbac® backing



**DESCRIPTION**

Cut pile carpet tile
Number of colourways: 16

**FLAMMABILITY**

EN 13501-1 B_{fl}-s1

**APPLICATION**

Heavy Contract:
Suitable for any type of heavy contract application.

**COLOUR FASTNESS**

Light: BS EN ISO 105-B02:1999: Better than 6
Rubbing: BS EN ISO 105-X12:1995: Wet 4-5, Dry 4-5
Water: BS EN ISO 105 E01:1996: Change of shade 4, Staining 5
Shampoo: BS 1006: Change of shade 4, Staining 5

**COMPOSITION**

100% PA Anso Performa Nylon 6
Stitch Density: 181,500 per m² ± 10%

**DIMENSIONAL STABILITY**

≤ 0.20% (EN986)

**PILE WEIGHT**

Pile weight: 1,050 gsm ± 10%
Total weight: 4,955 gsm ± 10%

**INSTALLATION METHOD**

Acrobat carpet tiles can be laid broadloom, 1/4 turn, or tessellated.

**BACKING**

Backing: Modified bitumen
Polyester primary and secondary
Also available in SOFTbac®

**STATIC PROPENSITY**

Body voltage: Pass (<2kV)
Computer anti-static to IBM/ICL: Yes
Lifetime protection through the use of permanent anti-static yarn and backing.

**DIMENSIONS**

50cm x 50cm
(Other sizes available for special orders)
Effective pile height: 5.0mm ± 0.5mm
Total thickness: 8.0mm ± 10%

**COMPRESSION RESISTANCE**

Static: Minimum 93% thickness recovery, 24 hours after removal of load.
Dynamic: Minimum 91% thickness recovery, after 1,000 impacts.

**CASTOR CHAIR**

Suitable for continuous degree of use (A):
Minimum R value: ≥ 2.4
BS EN 985: Test A 1995
Overall R value: 2.8

**ENVIRONMENTAL**

Materials used in the construction of the Acrobat range are chosen for their low volatile organic compound (VOC) levels.

INSTALLATION

Shades may vary from batch to batch and should be checked before installation. Batches should not be mixed in the same location. Tessera carpet tiles must be laid in accordance with the "Best Practice" techniques laid out in the Contract Flooring Association guidelines and BS5325. For additional information see the fitting instructions enclosed in each box of tiles.

**GUARANTEE**

Acrobat carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Tessera requirements currently in force.

MAINTENANCE

Regular power vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution. For additional information see the Clean and Care leaflet available free from Tessera. Test figures quoted are typical values obtained from internal and independent test evaluation.

For more information, contact your local Business Area Manager or ring 0870 8550 500.



BONAR FLOORS
Certificate Number FM22769
Carpet tiles manufactured at Bonar Floors (Bamber Bridge)
Under a quality assurance system approved to
BS EN ISO 9002 on behalf of Tessera Carpet Tiles.

Tessera®
Think Outside the Square

Chocflex®
Best in Class


BONAR FLOORS
The Hi-Performance Flooring Company

Flotex®
Engineered for Life

Coral® & Nuway®
Powerful Clean Off Systems

Bonar Floors, Unit 92, Seedlee Road, Walton Summit,
Preston, Lancashire PR5 8AE
Tel +44 (0)870 8550 500 Fax +44 (0)870 8550 535

Head Office Bonar Floors Ltd, High Holborn Road,
Ripley, Derbyshire DE5 3NT
Tel +44 (0)1773 744121 Fax +44 (0)1773 744142

Bonar Floors London Business Centre, Suite 105,
The Tea Building, 56 Shoreditch High Street, London E1 6JJ
Tel +44 (0)207 033 0335 Fax +44 (0)207 739 6035

customerservice@bonarfloors.com
www.bonarfloors.com